

# Data Sheet | Curved Windows

## DESCRIPTION

Curved (R5000) flush window with aluminium Driving Change (DC) frame and double acrylic glass for application in campervans.



## OPERATION

The top hung panel can be manually opened and closed with 3 handles. An ajar position for light ventilation is possible with the handles. Fixation of a larger window opening angles through telescopic strut stays with up to 3 positions, depending on the window height

SIZES (WxH)	CLAMPS	WEIGHT
280 x 380 mm	12	1.542 kg
490 x 500 mm	14	2.872 kg
560 x 465 mm	12	3.012 kg
700 x 510 mm	16	3.879 kg
750 x 465 mm	14	3.830 kg
818 x 315 mm	12	3.190 kg
960 x 450 mm	14	4.620 kg
985 x 465 mm	16	4.869 kg

The weight includes the installation parts

The ordering dimensions are equal to the cut-out sizes. To determine the other dimensions add or deduct the following:

Outer dimensions	+27 mm
Clearance	-55 mm

## MATERIAL SPECIFICATIONS

### System colour

Black

### Glass

Tinted scratch and UV-resistant double glazed cast acrylic in accordance with European standard E32 43R

### Frame

High strength powder-coated aluminium

### Handles

Black plastic

### Stays

Anodised aluminium telescopic strut stays with up to 3 positions

## INSTALLATION

Suitable for wall thicknesses 22-43 mm. See the next page for the available fixing clamps (not included). Order the required quantity of clamps and screws (included) separately. Make a hole with R80 corners. For metal walls of campervans: fit a (wooden) frame (not included) around the cut-out hole as an application base for the interior wall cladding (not included). Install the window with the clamps and screws. For replacements, glass stays, and handles are available separately.

## CLEANING

A soft damp cloth with mild detergent

## PACKAGING

Individual or bulk excluding clamps and screws.

## SPECIAL NOTE

Combine with curved Horrex UCS combi blinds and acrylic plates around the window exterior for a coordinated look.

## CURVED WINDOWS

### CLAMPS

Wall thickness:

22-23 mm

24-25 mm

26-27 mm

28-29 mm

30-31 mm

32-33 mm

34-35 mm

36-37 mm

38-39 mm

40-41 mm

42-43 mm



**Disclaimer | The specifications in this data sheet are for information purposes only and may be subject to change without prior notice**  
© Horrex 2021